


I: Intermill Logistics


Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

I: Intermill Logistics

Problem author: Maarten Sijm




Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Easier problem: Given time r , can the wheat be processed in time r or less?

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?


Easier problem: Given time r , can the wheat be processed in time r or less?

Observation: If you can reach i th windmill in time r (and get back), i.e., if $r \geq 2t_i$, you can process $p_i(r - 2t_i)$ kg wheat there. In total,

$$\sum_{i=1}^n \max(0, p_i(r - 2t_i)) .$$

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Easier problem: Given time r , can the wheat be processed in time r or less?


Observation: If you can reach i th windmill in time r (and get back), i.e., if $r \geq 2t_i$, you can process $p_i(r - 2t_i)$ kg wheat there. In total,

$$\sum_{i=1}^n \max(0, p_i(r - 2t_i)) .$$

Solution: We can *binary-search for the answer*. Travel times are positive integers, so $l = 2$ is a lower bound. For an upper bound, processing *all* wheat on the first machine takes $h = 2t_1 + w/p_1 \leq 2 \cdot 10^9$. Can now binary search for the correct value of r with $l \leq r \leq h$.

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Easier problem: Given time r , can the wheat be processed in time r or less?

Observation: If you can reach i th windmill in time r (and get back), i.e., if $r \geq 2t_i$, you can process $p_i(r - 2t_i)$ kg wheat there. In total,


$$\sum_{i=1}^n \max(0, p_i(r - 2t_i)) .$$

Solution: We can *binary-search for the answer*. Travel times are positive integers, so $l = 2$ is a lower bound. For an upper bound, processing *all* wheat on the first machine takes $h = 2t_1 + w/p_1 \leq 2 \cdot 10^9$. Can now binary search for the correct value of r with $l \leq r \leq h$.

Running time: $\mathcal{O}(n \log h)$.

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Easier problem: Given time r , can the wheat be processed in time r or less?

Observation: If you can reach i th windmill in time r (and get back), i.e., if $r \geq 2t_i$, you can process $p_i(r - 2t_i)$ kg wheat there. In total,

$$\sum_{i=1}^n \max(0, p_i(r - 2t_i)) .$$


Solution: We can *binary-search for the answer*. Travel times are positive integers, so $l = 2$ is a lower bound. For an upper bound, processing *all* wheat on the first machine takes $h = 2t_1 + w/p_1 \leq 2 \cdot 10^9$. Can now binary search for the correct value of r with $l \leq r \leq h$.

Running time: $\mathcal{O}(n \log h)$.

Statistics: 130 submissions, 43 accepted, 9 unknown

I: Intermill Logistics


Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

I: Intermill Logistics

Problem author: Maarten Sijm




Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Greedy solution: Sort the mills such that $t_1 \leq \dots \leq t_n$.

I: Intermill Logistics

Problem author: Maarten Sijm




Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Greedy solution: Sort the mills such that $t_1 \leq \dots \leq t_n$.

Claim: There is an optimal solution using exactly mills $1, \dots, i$ for some i , with the mills grinding for nonzero time, and either grinding or transporting during the entire makespan.

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Greedy solution: Sort the mills such that $t_1 \leq \dots \leq t_n$.

Claim: There is an optimal solution using exactly mills $1, \dots, i$ for some i , with the mills grinding for nonzero time, and either grinding or transporting during the entire makespan.

Implementation: Getting to/from mill i takes time t_i , so during that time the other mills can grind


$$w' = \sum_{j=1}^{i-1} p_j \cdot (2t_i - 2t_j) \text{ kg wheat.}$$

To grind the remaining wheat (if any), all i machines can work, so the makespan is

$$2t_i + (w - w') / (p_1 + \dots + p_i).$$

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Greedy solution: Sort the mills such that $t_1 \leq \dots \leq t_n$.

Claim: There is an optimal solution using exactly mills $1, \dots, i$ for some i , with the mills grinding for nonzero time, and either grinding or transporting during the entire makespan.

Implementation: Getting to/from mill i takes time t_i , so during that time the other mills can grind

$$w' = \sum_{j=1}^{i-1} p_j \cdot (2t_i - 2t_j) \text{ kg wheat.}$$


To grind the remaining wheat (if any), all i machines can work, so the makespan is

$$2t_i + (w - w') / (p_1 + \dots + p_i).$$

Running time: Naïve implementation requires $\mathcal{O}(n^2)$. The sums can be computed cumulatively to achieve time $\mathcal{O}(n \log n)$ for $n \geq 2$.

I: Intermill Logistics

Problem author: Maarten Sijm



Problem: For $i \in \{1, \dots, n\}$, the i th windmill can process p_i kg wheat in 1 hour; it takes t_i hours to travel to (and from). How fast can you process w kg wheat and get it back?

Greedy solution: Sort the mills such that $t_1 \leq \dots \leq t_n$.

Claim: There is an optimal solution using exactly mills $1, \dots, i$ for some i , with the mills grinding for nonzero time, and either grinding or transporting during the entire makespan.

Implementation: Getting to/from mill i takes time t_i , so during that time the other mills can grind

$$w' = \sum_{j=1}^{i-1} p_j \cdot (2t_i - 2t_j) \text{ kg wheat.}$$

To grind the remaining wheat (if any), all i machines can work, so the makespan is

$$2t_i + (w - w') / (p_1 + \dots + p_i).$$

Running time: Naïve implementation requires $\mathcal{O}(n^2)$. The sums can be computed cumulatively to achieve time $\mathcal{O}(n \log n)$ for $n \geq 2$.

Statistics: 130 submissions, 43 accepted, 9 unknown